

Dimensions of Flat-Bottom Tanks				
Capacity (L)	D I.D. (mm)	H Height (mm)	HR Roof (mm)	HC Cylinder (mm)
500	800	1,145	75	1,070
1,000	1,000	1,460	105	1,355
2,000	1,200	2,000	130	1,870
3,000	1,500	1,960	170	1,790
5,000	1,900	2,080	220	1,860
8,000	2,000	2,920	240	2,680
10,000	2,500	2,450	305	2,145
15,000	2,800	2,910	345	2,565
20,000	2,800	3,765	345	3,420
30,000	2,800	5,475	345	5,130
40,000	3,000	6,330	370	5,960
50,000	3,400	6,220	420	5,800
80,000	3,600	8,730	455	8,275
100,000	4,000	8,880	500	8,380
150,000	4,000	13,070	500	12,570
200,000	4,000	17,260	500	16,760

Dimensions of Conical-Bottom Tanks			
Capacity (L)	I.D. (mm)	Height (mm)	Cone Height 120° (mm)
500	800	1,620	230
1,000	1,000	1,950	290
2,000	1,200	2,505	350
3,000	1,500	2,480	430
5,000	1,900	2,630	550
7,000	2,000	3,140	580
10,000	2,500	3,030	725
12,000	2,800	2,945	810
15,000	3,000	3,210	865
20,000	3,400	3,375	980
25,000	3,600	3,680	1,040
30,000	4,000	3,685	1,155

**formoplast also offers custom sizes and tailor-made designs in accordance with your specifications.**

Tanks are also available with

- Stirrer mounts
- 60°, 90° and 120° conical bottoms, mounted on base frame

Additional accessories and peripheral equipment available.

